NEWARE

Specifications

BTS4000-5V6A Battery testing system										
Model:	BTS4000-	5	V	6	A	Battery Testing System	SN:	CT-4008Q	-5V6A	-S1

Items		**Values**
Input AC		AC 220V/110V ±10% / 50Hz
Input power		400 W
Resolution		AD: 24bit; DA: 16bit
Input impedance		≥1MΩ
Voltage	CV output range	10mV~5V
	Min discharge voltage	1V for universal holder,1.5V for 2m cable
	Accuracy	± 0.02% of FS
	Stability	± 0.02% of FS
Current	Output range/channel	**Range1: 0.2mA-100mA; Range2: 100mA-500mA; Range3: 500mA-3A; Range4: 3A-6A**
	Accuracy	± 0.02% of FS
	CV cut-off current	Range1: 0.1mA; Range2: 0.5mA; Range3: 3mA; Range4: 6mA
	Stability	± 0.02% of FS
Power	Output power/channel	30 W
	Stability	± 0.02% FS
Time	Current response time	<1.5ms (10%FS~90%FS)
	Working step time	≤(365*24)h/step Timeformat-00:00:00.000(h, m, s, ms)
Data record	Data record conditions	Min data record interval: 100ms
		Min voltage change: 5mV
		Min current change: 0.1mA; 0.5mA; 3mA; 6mA
	Frequency	10Hz
Charge	Charge modes	CC, CV, CCCV, CP
	Cut-off condition	Voltage, Current, Time, Capacity, Energy, -△V
Discharge	Discharge modes	CC, CV, CCCV, CP, CR
	Cut-off condition	Voltage, Current, Time, Capacity, Energy
Pulse	Charge	CC, CP
	Discharge	CC, CP
	Min pulse width	500ms
	Pulse counts	Up to 32
	Chg and Dschg switch	Supported
	Cut-off condition	Voltage, Time
DCIR	Calculated DCIR values available in BTSDA	
Cycle	Max cycles	65535
	Max steps	254
	Cycle nest	3
Protection	Safety protection	• Power-failure data protection
		• Offline operation mode
		• User-defined protection conditions, such as upper and lower limited current/voltage, delay time, temperature, etc.

Web: neware.co.kr Tel: 010-9345-0834 E-mail: sales@neware.co.kr

NEWARE

Specifications

Channels feature	Independent pairs of closed loop for constant current and voltage
Channels control mode	Independent control
Data acquisition method	Kelvin connection
Noise	<55dB
Database	MySQL
Communication	TCP/IP
Operating system	Windows 7/8/10
Data export	EXCEL, TXT, CSV, PDF, Plot/Graph
Min. disk drive	500GB
Communication port	Ethernet port
Leak Current	<5μA
Channels per unit	8
Operation and storage environment requirement	
Items	**Values**
Operation environment temperature	0℃~40℃ (When the temperature is 25±5℃, the accuracy offset caused by temperature is less than 50ppm /℃)
Storage environment temperature	-10℃~50℃
Operation environment humidity	≤70% RH(no moisture condensation)
Storage environment humidity	≤80% RH(no moisture condensation)
Clamps and dimensions	
Items	**Values**
Tester pictures	 
Clamps pictures	    Universal holder | Alligator | Polymer | Ring connector Pictures just for reference
Dimensions(W*D*H)(mm)	3U（19"）, 483*404*130

Web: neware.co.kr Tel: 010-9345-0834 E-mail: sales@neware.co.kr